



## TECHNIQUES

### TECHNOLOGIE HYBRID

<b>MOTEUR</b>	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
<b>ECRAN</b>	Giant RideControl Ergo3, grip integrated remote
<b>COMMANDE</b>	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
<b>BATTERIE</b>	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible (exclude S size)
<b>CHARGEUR</b>	Giant EnergyPak 6A smart charger, 60% in 2:15h
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile

### CADRE

<b>TAILLES</b>	S, M, L, XL
<b>COLORIS</b>	Blue Dragonfly / Black
<b>CADRE</b>	ALUXX SL-grade aluminum, Advanced Forged Composite Upper Rocker, 160mm Maestro suspension system, 'Boost' 148x12mm, Universal Derailleur Hanger
<b>FOURCHE</b>	Fox 38 Float Factory GRIP 2 Air 170 matt black 1111-38FLOA-0024
<b>AMORTISSEUR</b>	Fox X2 Factory, EVOL Large Volume sleeve, 205x62.5mm Trunnion mount, custom tuned, recommended sag: 30%

### COMPOSANTS

<b>CINTRE</b>	Giant Contact Trail, 35x800mm
<b>POIGNÉES</b>	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
<b>POTENCE</b>	Giant Contact SL 35
<b>TIGE DE SELLE</b>	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
<b>SELLE</b>	Giant Romero Trail
<b>PÉDALES</b>	Flat pedal
<b>DÉRAILLEUR</b>	
<b>MANETTES</b>	Shimano XT LinkGlide
<b>DÉRAILLEUR AVANT</b>	MRP HD2 co-moulded chain guide
<b>DÉRAILLEUR ARRIÈRE</b>	Shimano XT LinkGlide 11-speed, Shadow+
<b>FREINS</b>	Shimano XT, BR-8120, 4-piston, hydraulic disc, RT66, 220mm
<b>LEVIERS DE FREIN</b>	Shimano XT, I-spec EV
<b>CASSETTE</b>	Shimano Cues LinkGlide, CS-LG400-11, 11-50T, 11-speed
<b>CHAÎNE</b>	Shimano LinkGlide, CN-LG500
<b>PÉDALIER</b>	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-HD forged crankarm set (S/M:160mm, L/XL:165mm)
<b>BOITIER DE PÉDALIER</b>	n/a

### ROUES

<b>JANTES</b>	E-TRA Hookless Tubeless ready Alloy 29 [F] / 27.5 [R], 30mm inner width
<b>MOYEURS</b>	E-TRA MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 Shimano HG Drive Body Pawl Driver (3 Pawl 30T) Thru-axle [R]
<b>RAYONS</b>	Sapim E-Lite [R] Race [F], e-bike optimized
<b>PNEUS</b>	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra[F] Maxxis High Roller II 27.5x2.5" foldable, Tubeless, DoubleDown, 3C MaxxTerra Compound [R]
<b>EXTRAS</b>	Tubeless kit (liquid, valves, levers, manual, tool)

### ACCESSOIRES

<b>ECLAIRAGE</b>	Kit d'éclairage avant et arrière à piles
<b>ANTI-VOL</b>	Torx 25 Battery Lock with built-in Torque limiter

### LIMITES

<b>POIDS TOTAL MAX AUTORISÉ</b>	156 kg (vélo, cycliste et bagages)
---------------------------------	------------------------------------

**Prix Public Conseillé: 7 300,00 €**

## GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Seat Post Insertion Depth (mm)	230	260	280	310				
Angle de tube de selle	76,7°   77,5°	76,7°   77,5°	76,7°   77,5°	76,7°   77,5°				
Longueur du tube supérieur (mm)	569   568	595   594	622   621	649   648				
Longueur du tube de direction (mm)	100	100	110	120				
Angle du tube de direction	63,7°   64,5°	63,7°   64,5°	63,7°   64,5°	63,7°   64,5°				
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	135,5   132,1	135   132	135   132	135,5   132,1				
Empattement (mm)	1209   1210	1236   1237	1265   1266	1295   1296				
Longueur des bases (mm)	457   455	454   454	454   454	454   454				
Drop du boîtier de pédalier (mm)	25   15	25   15	25   15	25   15				
Stack (mm)	636   632	635   632	645   641	654   650				
Reach (mm)	425   430	450   455	475   480	500   505				
Hauteur en statique (mm)	785   789	772   776	771   775	768   772				
Largeur de cintre (mm)	800	800	800	800				
Longueur de potence (mm)	40	40	40	50				
Longueur des manivelles (mm)	160	160	165	165				
Diamètre des roues	29"	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]				

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.