



## TECHNIQUES

CADRE	
<b>TAILLES</b>	XS, S, M, M/L, L, XL
<b>COLORIS</b>	Carbon / Solar Flare
<b>CADRE</b>	Advanced-grade composite, 12x142mm thru-axle, disc
<b>FOURCHE</b>	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
COMPOSANTS	
<b>CINTRE</b>	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
<b>POIGNÉES</b>	Stratus Lite 3.0
<b>POTENCE</b>	Giant Contact AeroLight, -10 degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
<b>TIGE DE SELLE</b>	Giant D-Fuse, composite, 14mm offset
<b>SELLE</b>	Giant Grit
DÉRAILLEUR	
<b>MANETTES</b>	Shimano GRX RX-610, 2x12
<b>DÉRAILLEUR AVANT</b>	Shimano GRX RX-820
<b>DÉRAILLEUR ARRIÈRE</b>	Shimano GRX RX-820
<b>FREINS</b>	Shimano GRX RX-400 HRD, Giant MPH rotors [F]160mm, [R]160mm
<b>LEVIERS DE FREIN</b>	Shimano GRX RX-610 hydraulic
<b>CASSETTE</b>	Shimano CS-HG710, 12-speed, 11x36
<b>CHAÎNE</b>	KMC X12L-1
<b>PÉDALIER</b>	FSA Omega Modular AGX+, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOITIER DE PÉDALIER</b>	FSA BB-AL86, press fit

ROUES	
<b>JANTES</b>	Giant P-X2 Disc wheelset, alloy
<b>MOYEUX</b>	Giant alloy, 12mm thru-axle
<b>RAYONS</b>	Sapim
<b>PNEUS</b>	Giant Crosscut Grip TR, 700x40c, tubeless
<b>EXTRAS</b>	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, in-frame storage bag
ACCESSOIRES	
<b>ECLAIRAGE</b>	Kit d'éclairage avant et arrière à piles

**Prix Public Conseillé: 3 100,00 €**

## GÉOMÉTRIE

CADRE	XS	S	M	ML	L
	SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT	LONG SHORT   LONG SHORT
Longueur de tube de selle (mm)	430	450	470	490	510
Angle de tube de selle	74,0°	73,5°	73,5°	73,0°	73,0°
Longueur du tube supérieur (mm)	540	550	560	575	585
Longueur du tube de direction (mm)	125	135	150	165	180
Angle du tube de direction	70,0°	71,0°	71,5°	72,0°	72,0°
Déport de fourche (mm)	50	50	50	50	50
Trail (mm)	78   82	72   75	68   72	65   68	65   68
Empattement (mm)	1024   1034	1020   1030	1026   1036	1031   1041	1041   1051
Longueur des bases (mm)	425   435	425   435	425   435	425   435	425   435
Drop du boîtier de pédalier (mm)	80   81	80   81	80   81	80   81	80   81
Stack (mm)	556	570	586	602	616
Reach (mm)	381	381	387	391	397
Hauteur en statique (mm)	724   731	740   747	757   764	774   780	791   797
Largeur de cintre (mm)	420	420	440	440	460
Longueur de potence (mm)	50	60	70	80	80
Longueur des manivelles (mm)	170	170	172,5	172,5	175
Diamètre des roues	700c	700c	700c	700c	700c

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.