

TRANCE X E+ 2



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	SyncDrive Pro 2, 85Nm, powered by Yamaha
ECRAN	Giant RideControl Ergo3, grip integrated remote
COMMANDE	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIE	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGEUR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COLORIS	Messier / Black
CADRE	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FOURCHE	Fox 36 Float Rhythm E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Sweep adjust, Boost 110x15QR
AMORTISSEUR	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Contact 35 Trail, 35x780mm
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	OBC Giant Contact Switch AT Travel adjustable 172D-CONTAC-0053 total length 315 T100-70MM / 172D-CONTAC-0052 total length 395 T140-110MM / 172D-CONTAC-0051 total length 470 T170 -140MM / 172D-CONTAC-0050 total length 530 T200-170MM
SELLE	Giant Romero E
PÉDALES	Flat pedal
DÉRAILLEUR	
MANETTES	Shimano SLX
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano SLX, 12-speed, Shadow+
FREINS	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
LEVIER DE FREIN	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProteq, e-bike optimized
PÉDALIER	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29"
MOYEUX	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
ANTI-VOL	Torx 25 Battery Lock with built-in Torque limiter
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 5 300,00 €

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW HIGH		LOW HIGH		LOW HIGH		LOW HIGH	
Longueur de tube de selle (mm)	400		425		450		475	
Angle de tube de selle	76,0° 76,7°		76,0° 76,7°		76,0° 76,7°		76,0° 76,7°	
Longueur du tube supérieur (mm)	577 575		610 605		637 635		667 665	
Longueur du tube de direction (mm)	95		100		110		120	
Angle du tube de direction	65,7° 66,5°		65,8° 66,5°		65,8° 66,5°		65,8° 66,5°	
Déport de fourche (mm)	44		44		44		44	
Trail (mm)	117 122,4		117 122,4		117 122,4		117 122,4	
Empattement (mm)	1205 1206		1239 1237		1268 1269		1300 1301	
Longueur des bases (mm)	473 473		473 473		473 473		473 473	
Drop du boîtier de pédalier (mm)	30 20		30 20		30 20		30 20	
Stack (mm)	606 601		611 605		621 614		630 624	
Reach (mm)	439 447		457 462		482 489		510 517	
Hauteur en statique (mm)	783 789		775 784		763 770		775 782	
Largeur de cintre (mm)	780		780		780		780	
Longueur de potence (mm)	40		50		50		60	
Longueur des manivelles (mm)	160		165		165		170	
Diamètre des roues	29"		29"		29"		29"	

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.