



TECHNIQUES

CADRE	
TAILLES	XXS, XS, S, M, L
COLORIS	Mechanic Rose
CADRE	Advanced-Grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	Liv Contact XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
POIGNÉES	Liv Stratus Elite 2.0
POTENCE	Giant Contact AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
TIGE DE SELLE	Giant Variant, composite, -5/+15mm offset
SELLE	Liv Approach
DÉRAILLEUR	
MANETTES	Shimano 105 Di2
DÉRAILLEUR AVANT	Shimano 105 Di2 FD-R7150
DÉRAILLEUR ARRIÈRE	Shimano 105 Di2 RD-R7150
FREINS	Shimano 105 Di2 hydraulic, Giant MPH rotors [F] 160mm, [R] 140mm
LEVIERS DE FREIN	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x34
CHAÎNE	KMC X12L-1
PÉDALIER	Shimano 105, 36/52 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOITIER DE PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant P-R2, [F] 25mm, [R] 25mm
MOYEUX	12mm thru-axle
RAYONS	stainless
PNEUS	Giant Gavia Course 1, tubeless, 700x25c (28mm effective), folding
EXTRAS	tubeless prepared, 33mm max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 3 500,00 €

GÉOMÉTRIE

CADRE	XXS	XS	S	M	L
Longueur de tube de selle (mm)	390	420	450	480	510
Angle de tube de selle	75,0°	75,0°	74,5°	74,0°	73,5°
Longueur du tube supérieur (mm)	498	508	524	540	555
Longueur du tube de direction (mm)	105	120	135	155	175
Angle du tube de direction	70,0°	71,0°	72,0°	72,5°	72,5°
Déport de fourche (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Empattement (mm)	970	973	977	984	994
Longueur des bases (mm)	405	405	405	405	405
Drop du boitier de pédalier (mm)	72	72	69,5	69,5	69,5
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Hauteur en statique (mm)	685	707	736	763	783
Largeur de cintre (mm)	360	360	380	400	420
Longueur de potence (mm)	80	80	90	100	110
Longueur des manivelles (mm)	165	165	170	170	172,5
Diamètre des roues	700C	700C	700C	700C	700C

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.