



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Asphalt Green, Solar Flare
CADRE	ALUXX SL-grade aluminum front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle
FOURCHE	Giant Crest SL, 130mm, 15x110, 44mm offset
AMORTISSEUR	Giant Crest, 185/50, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact TR35, 780x35mm
POIGNÉES	Giant Trail S:120mm, M:120mm, L:130mm, XL:130mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm
SELLE	Giant Romero
PÉDALES	platform [GC,GT]
DÉRAILLEUR	
MANETTES	Shimano Deore, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano Deore, Shadow +
FREINS	Shimano Deore BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
LEVIERS DE FREIN	Shimano BL-MT401
CASSETTE	Shimano Deore, 10x51
CHAÎNE	KMC X-12
PÉDALIER	Praxis Cadet M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOITIER DE PÉDALIER	Praxis, press fit

ROUES	
JANTES	Giant TRA 2.29 Carbon WheelSystem, 30mm inner width
MOYEURS	Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAYONS	Sapim
PNEUS	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.6" max tire size, 34t max chainring size

Prix Public Conseillé: 2 800,00 €

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	420	430	465	496				
Seat Post Insertion Depth (mm)	290	300	335	366				
Angle de tube de selle	77,2° 78,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°
Longueur du tube supérieur (mm)	561 559	599 597	626 624	663 661				
Longueur du tube de direction (mm)	100	110	120	130				
Angle du tube de direction	65,4° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	126 120	126 120	126 120	126 120				
Empattement (mm)	1166 1165	1195 1194	1124 1123	1263 1262				
Longueur des bases (mm)	439 437	439 437	439 437	439 437				
Drop du boîtier de pédalier (mm)	45 35	45 35	45 35	45 35				
Stack (mm)	610 604	619 613	628 622	637 631				
Reach (mm)	422 431	447 456	472 480	507 515				
Hauteur en statique (mm)	730 738	725 734	749 759	771 781				
Largeur de cintre (mm)	780	780	780	780				
Longueur de potence (mm)	40	40	50	50				
Longueur des manivelles (mm)	165	170	170	170				
Diamètre des roues	29"	29"	29"	29"				

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.