



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Sandstorm
CADRE	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FOURCHE	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTISSEUR	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact TR35, alloy, 780x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLE	Giant Romero SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Shimano Deore, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano Deore, Shadow +
FREINS	Shimano BR-MT420, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
LEVIERS DE FREIN	Shimano Deore BL-MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAÎNE	KMC X-12
PÉDALIER	Praxis Cadet HD M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOITIER DE PÉDALIER	Praxis, press fit

ROUES	
JANTES	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
MOYEURS	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
RAYONS	Sapim, 28, J-bend
PNEUS	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 3 500,00 €

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Angle de tube de selle	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Longueur du tube supérieur (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Longueur du tube de direction (mm)	100			105			115			125		
Angle du tube de direction	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Déport de fourche (mm)	44			44			44			44		
Trail (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133,9	131,3	128,5
Empattement (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1281	1280
Longueur des bases (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Drop du boîtier de pédalier (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Hauteur en statique (mm)	732	737	742	746	750	755	763	768	773	781	786	791
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			50			50		
Longueur des manivelles (mm)	165			170			170			170		
Diamètre des roues	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.