

INTRIGUE X ADVANCED E+ ELITE 1



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	SyncDrive Pro2 85Nm, powered by Yamaha
ECRAN	RideControl Ergo 3, RideControl GO integrated in T/T
COMMANDE	ANT+ Wireless display compatible
BATTERIE	EnergyPak Smart Compact 400, EnergyPak Plus range extender compatible
CADRE	
TAILLES	XS, S, M, L
COLORIS	Airglow
CADRE	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension systemMX (front 29", rear 27.5")
FOURCHE	Fox 36 Performance Elite Live Valve E-Tuned, 29er, 150mm travel, 44mm offset, Fit4 damper, Kabolt-X 110, electronic adaptive suspension, e-bike integrated
AMORTISSEUR	Fox Float X Live Valve, 185x52.5mm Trunnion mount, electronic suspension, e-bike integrated
COMPOSANTS	
CINTRE	Giant Contact SLR Trail, carbon, 760mm (XS-S), 800mm (M-L)
POIGNÉES	Liv Tactal Pro-E Single Lock-On Grips
POTENCE	Giant Contact SLR Trail, integrated, 40/45/50mm Reach, 7/9degree Sweep Adjust System
TIGE DE SELLE	Rad+ travel adjust dropper, dropper, 30,9mm (XS&S:100~140mm/ M:140~170mm/ L:170~200mm)
SELLE	Liv Sylvia E+
PÉDALES	n/a
DÉRAILLEUR	
MANETTES	SRAM AXS Rocker Paddle, wireless electronic shifting
DÉRAILLEUR AVANT	MRP 1X HD2 custom co-molded chain guide
DÉRAILLEUR ARRIÈRE	SRAM GX Eagle AXS
FREINS	SRAM Code R, hydraulic disc, 220mm[F] / 200mm[R]
LEVIER DE FREIN	SRAM Code R
CASSETTE	SRAM XG-1275, 10-52T, 12-speed
CHAÎNE	SRAM GX Eagle PowerLock
PÉDALIER	Praxis Performance Carbon e-crank arms (XS/S:160, M/L:165) SRAM X-SYNC Eagle 36T chain ring
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	TRX 2 Hookless Clincher, 29" [F] / 27.5" [R], 30mm inner width
MOYEUX	TRX 2 MTB Alloy Hub, 6 Bolt, Pawl Driver (3 Pawl 24T) SRAM XD, 110 x 15 [F] / 148 x 12 [R] Thru-axle
PNEUS	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 8 600,00 €

GÉOMÉTRIE

CADRE	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Longueur de tube de selle (mm)	380	400	425	450
Angle de tube de selle	77,2° 78,0°	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°
Longueur du tube supérieur (mm)	557 555	572 570	597 595	622 620
Longueur du tube de direction (mm)	95	95	100	115
Angle du tube de direction	65,7° 66,5°	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°
Déport de fourche (mm)	44	44	44	44
Trail (mm)	113 108	113 108	113 108	113 108
Empattement (mm)	1174 1175	1188 1190	1200 1201	1228 1229
Longueur des bases (mm)	447 447	447 447	447 447	447 447
Drop du boitier de pédalier (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	606 601	611 605	625 619
Reach (mm)	419 427	434 442	444 452	466 473
Hauteur en statique (mm)	722 730	726 735	717 726	711 723
Largeur de cintre (mm)	760	760	800	800
Longueur de potence (mm)	40	40	40	50
Longueur des manivelles (mm)	160	160	165	165
Diamètre des roues	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.