



TECHNIQUES

CADRE	
TAILLES	27.5": XS, S, 29": S, M, L
COLORIS	Asphalt Green
CADRE	ALUXX-grade aluminum, disc
FOURCHE	Giant SXC32-2 RCL Alloy SingleAir 29"/27.5" 15x110 TA 1.5" Taper steerer 27.5" XS/S: 80mm, S/M/L: 100mm 29"
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Connect Trail, 31.8mm 27.5" XS/S: 690mm, S/M/L: 750mm
POIGNÉES	Giant Sole-O
POTENCE	Giant Sport, 7-degree XS/S: 40mm, 29" M/L: 50mm
TIGE DE SELLE	Giant Contact Swith Core, 30.9mm, XS/S: 100x350mm, M/L: 100x400mm
SELLE	Contact Ergo
PÉDALES	MTB caged
DÉRAILLEUR	
MANETTES	Shimano Deore M6100, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano Deore M6100, Shadow +
FREINS	Shimano BR-MT200, hydraulic, Shimano RT-10 rotors [F]180mm, [R]160mm
LEVIERS DE FREIN	Shimano Deore BL-MT200
CASSETTE	Shimano Deore M6100, 10x51
CHAÎNE	KMC X12
PÉDALIER	ProWheel MPX, 32t (27.5") or 30t (29") 27.5" XS/S: 165mm, S/M/L: 170mm 29"
BOITIER DE PÉDALIER	power spline

ROUES	
JANTES	27.5": Giant GX03V 27.5", alloy, double wall, 21mm inner width 29": Giant GX03V 29", alloy, double wall, 21mm inner width
MOYEUX	Shimano, sealed bearing
RAYONS	stainless, 14g
PNEUS	Maxxis Recon Race 27.5x2.4" or 29x2.4", 60tpi wire bead
EXTRAS	2.4" max tire size, max chainring 32T

Prix Public Conseillé: 1 150,00 €

GÉOMÉTRIE

CADRE	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Longueur de tube de selle (mm)	330	365	380	410	450
Seat Post Insertion Depth (mm)	280	310	330	360	220
Angle de tube de selle	74,0°	74,0°	74,5°	74,5°	74,0°
Longueur du tube supérieur (mm)	538	558	571	599	610
Longueur du tube de direction (mm)	90	95	90	100	105
Angle du tube de direction	67,0°	67,0°	67,5°	67,5°	68,5°
Déport de fourche (mm)	44	44	44	44	51
Trail (mm)	105,2	105,2	108,9	108,9	94,3
Empattement (mm)	1080	1101	1129	1158	1160
Longueur des bases (mm)	440	440	455	455	455
Drop du boitier de pédalier (mm)	45	45	55	55	55
Stack (mm)	548	553	593	602	610
Reach (mm)	381	400	407	432	435
Hauteur en statique (mm)	680	689	689	708	757
Largeur de cintre (mm)	690	690	690	690	750
Longueur de potence (mm)	40	40	40	50	50
Longueur des manivelles (mm)	165	165	170	170	175
Diamètre des roues	27.5"	27.5"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.